

Lead-acid Replacement Battery

N12&N24 Series

Model Parameters

Model	Voltage (V)	Capacity(Ah)	Dimension (W*L*H)	Weight(Kg)	Bluetooth	CAN	RS485	Heating	LCD	Active equalization
N6-8	6.4	8	151*50*93	0.54	N	N	N	N	N	N
N6-12	6.4	12	151*50*93	0.66	N	N	N	N	N	N
N12-6	12.8	6	90*70*101	0.66	N	N	N	N	N	N
N12-8	12.8	8	151*65*97	1.1	N	N	N	N	N	N
N12-12	12.8	12	151*65*97	1.3	N	N	N	N	N	N
N12-30	12.8	30	181*70*156	3	N	N	N	N	N	N
N12-40	12.8	40	174*165*125	4.5	N	N	N	N	N	N
N12-50	12.8	50	165*126*175	5.8	N	N	N	N	N	N
N12-60	12.8	60	198*166*170	6.8	N	N	N	N	N	N
N12-75	12.8	75	198*166*170	7.9	N	N	N	N	N	N
N12-100M	12.8	100	260*168*209	9.5	N	N	N	N	N	N
N12-100	12.8	100	260*168*209	9.5	N	N	N	N	N	N
N12-100B	12.8	100	395*110*293	10.5	N	N	N	N	N	N
N12-150	12.8	150	330*171*220	15.5	N	N	N	N	N	N
N12-200	12.8	200	483*170*240	18.5	N	N	N	N	N	N
N12-200B	12.8	200	552*110*288	20	N	N	N	N	N	N
N12-300	12.8	300	345*190*245	27	N	N	N	N	N	N
N12-400	12.8	400	522*238*223	37	N	N	N	N	N	N
N24-6	25.6	6	151*65*97	1.3	N	N	N	N	N	N
N24-50	25.6	50	260*168*209	9.5	N	N	N	N	N	N
N24-100	25.6	100	483*170*240	18.5	N	N	N	N	N	N
N24-200	25.6	200	522*238*223	37	N	N	N	N	N	N



Long Lifespan
15 years design life



Multiple series and parallel
Support multiple series/parallel use



High Efficiency
Efficient battery management system



Multifunction
Active Equalizer, Bluetooth,
and display (optional)



High Security
The safest lithium iron phosphate
battery technology

Product Introduction

Namkoo power uses LFP cells on basis of retaining the appearance of standard lead-acid, batteries to develop high-energy density, high-safety, and intelligent lithium lon battery products. Covering two voltage specifications, such as 12V, 24V. Our product supports 4 units in series and 4 units in parallel connection.